


1. REFER TO UDOT STD DWG PV 6 FOR RUMBLE STRIP DETAILS.
2. CENTER PAINT STRIPES ON RUMBLE STRIPS.
3. PLACE RUMBLE STRIPS ON DOWN STREAM SIDE OF BROKEN LINES WHEN PRACTICAL.
4. FLUSH COAT ALL RUMBLE STRIPS.

2. CENTER PAINT STRIPES ON RUMBLE STRIPS.
3. PLACE RUMBLE STRIPS ON DOWN STREAM SIDE OF BROKEN LINES WHEN PRACTICAL.
4. FLUSH COAT ALL RUMBLE STRIPS.



TYPICAL TWO-WAY WITH PASSING
PERMISSIVE IN ONE DIRECTION

TYPICAL TWO-WAY WITH PASSING
PERMISSIVE IN BOTH DIRECTION

TYPICAL TWO-WAY WITH FLUSH MEDIAN

RUMBLE STRIPS CENTERLINE APPLICATION

UTAH DEPARTMENT OF TRANSPORTATION
STANDARD DRAWINGS FOR ROAD AND BRIDGE CONSTRUCTION
SCALE: 1"=10'-0"

RECOMMENDED FOR APPROVAL _____ DATE APR. 26, 2007

CHAIRMAN STANDARDS COMMITTEE _____ DATE APR. 26, 2007

APPROVED _____ DATE _____

DEPUTY DIRECTOR _____

STANDARD DRAWING TITLE

STD DWG
PV 8

[illegible]

28-MAY-2007